This paper is a part of the hereunder thematic dossier published in OGST Journal, Vol. 69, No. 5, pp. 773-969 and available online [here](#)

Cet article fait partie du dossier thématique ci-dessous publié dans la revue OGST, Vol. 69, n°5, pp. 773-969 et téléchargeable [ici](#)

DOSSIER Edited by/Sous la direction de : **P.-L. Carrette**

PART 1

Post Combustion CO₂ Capture Captage de CO₂ en postcombustion

Oil & Gas Science and Technology – Rev. IFP Energies nouvelles, Vol. 69 (2014), No. 5, pp. 773-969

Copyright © 2014, IFP Energies nouvelles

- 773 > Editorial
- 785 > *CO₂ Capture Rate Sensitivity Versus Purchase of CO₂ Quotas. Optimizing Investment Choice for Electricity Sector*
Sensibilité du taux de captage de CO₂ au prix du quota européen. Usage du faible prix de quota européen de CO₂ comme effet de levier pour lancer le déploiement de la technologie de captage en postcombustion
P. Coussy and L. Raynal
- 793 > *Emissions to the Atmosphere from Amine-Based Post-Combustion CO₂ Capture Plant – Regulatory Aspects*
Émissions atmosphériques des installations de captage de CO₂ en postcombustion par les amines – Aspects réglementaires
M. Azzi, D. Angove, N. Dave, S. Day, T. Do, P. Feron, S. Sharma, M. Attalla and M. Abu Zahra
- 805 > *Formation and Destruction of NDELA in 30 wt% MEA (Monoethanolamine) and 50 wt% DEA (Diethanolamine) Solutions*
Formation et destruction de NDELA dans des solutions de 30% de MEA (monoéthanolamine) et de 50% de DEA (diéthanolamine)
H. Knuutila, N. Asif, S. J. Vevelstad and H. F. Svendsen
- 821 > *Validation of a Liquid Chromatography Tandem Mass Spectrometry Method for Targeted Degradation Compounds of Ethanolamine Used in CO₂ Capture: Application to Real Samples*
Validation d'une méthode de chromatographie en phase liquide couplée à la spectrométrie de masse en tandem pour des composés de dégradation ciblés de l'éthanolamine utilisée dans le captage du CO₂ : application à des échantillons réels
V. Cuzuel, J. Brunet, A. Rey, J. Dugay, J. Vial, V. Pichon and P.-L. Carrette
- 833 > *Equilibrium and Transport Properties of Primary, Secondary and Tertiary Amines by Molecular Simulation*
Propriétés d'équilibre et de transport d'amines primaires, secondaires et tertiaires par simulation moléculaire
G. A. Orozco, C. Nieto-Draghi, A. D. Mackie and V. Lachet
- 851 > *CO₂ Absorption by Biphasic Solvents: Comparison with Lower Phase Alone*
Absorption du CO₂ par des solvants biphasiques : comparaison avec la phase inférieure isolée
Z. Xu, S. Wang, G. Qi, J. Liu, B. Zhao and C. Chen
- 865 > *Kinetics of Carbon Dioxide with Amines – I. Stopped-Flow Studies in Aqueous Solutions. A Review*
Cinétique du dioxyde de carbone avec les amines – I. Étude par stopped-flow en solution aqueuse. Une revue
G. Couchaux, D. Barth, M. Jacquin, A. Faraj and J. Grandjean
- 885 > *Modeling of the CO₂ Absorption in a Wetted Wall Column by Piperazine Solutions*
Modélisation de l'absorption de CO₂ par des solutions de pipérazine dans un film tombant
A. Servia, N. Laloue, J. Grandjean, S. Rode and C. Roizard
- 903 > *Piperazine/N-methylpiperazine/N,N'-dimethylpiperazine as an Aqueous Solvent for Carbon Dioxide Capture*
Mélange pipérazine/N-méthylpipérazine/N,N'-diméthylpipérazine en solution aqueuse pour le captage du CO₂
S. A. Freeman, X. Chen, T. Nguyen, H. Rafique, Q. Xu and G. T. Rochelle
- 915 > *Corrosion in CO₂ Post-Combustion Capture with Alkanolamines – A Review*
Corrosion dans les procédés utilisant des alcanolamines pour le captage du CO₂ en postcombustion
J. Kittel and S. Gonzalez
- 931 > *Aqueous Ammonia (NH₃) Based Post-Combustion CO₂ Capture: A Review*
Captage de CO₂ en postcombustion par l'ammoniac en solution aqueuse (NH₃) : synthèse
N. Yang, H. Yu, L. Li, D. Xu, W. Han and P. Feron
- 947 > *Enhanced Selectivity of the Separation of CO₂ from N₂ during Crystallization of Semi-Clathrates from Quaternary Ammonium Solutions*
Amélioration de la sélectivité du captage du CO₂ dans les semi-clathrates hydratés en utilisant les ammoniums quaternaires comme promoteurs thermodynamiques
J.-M. Herri, A. Bouchemoua, M. Kwaterski, P. Brântuas, A. Galfré, B. Bouillot, J. Douzet, Y. Ouabbas and A. Cameirao
- 969 > Erratum
J. E. Roberts

Kinetics of Carbon Dioxide with Amines. I. Stopped-Flow Studies in Aqueous Solutions. A Review

Gabriel Couchaux^{1,2}, Danielle Barth², Marc Jacquin¹, Abdelaziz Faraj³ and Julien Grandjean^{1*}

¹ IFP Energies nouvelles, Rond-point de l'échangeur de Solaize, BP 3, 69360 Solaize - France

² Laboratoire Réactions et Génie des Procédés, UPR CNRS 3349, Université de Lorraine,
1 rue Grandville, BP 20451, 54001 Nancy Cedex - France

³ IFP Energies nouvelles, 1-4 avenue de Bois-Préau, 92852 Reuil-Malmaison - France

e-mail: gabriel.couchaux@ifpen.fr - danielle.barth@ensic.inpl-nancy.fr - marc.jacquin@ifpen.fr - abdelaziz.faraj@ifpen.fr
julien.grandjean@ifpen.fr

* Corresponding author

Résumé — Cinétique du dioxyde de carbone avec les amines – I. Étude par *stopped-flow* en solution aqueuse. Une revue — Il est possible de trouver de nombreuses informations sur la cinétique de réaction amine-CO₂ dans la littérature. Toutefois, comme il existe plusieurs techniques expérimentales et plusieurs mécanismes réactionnels possibles, on observe parfois une grande dispersion des résultats expérimentaux avec diverses interprétations. Dans cet article, une méthode qui permet de comparer les constantes cinétiques obtenues par différents auteurs est proposée. D'abord nous présentons les différentes techniques expérimentales et justifions de comparer les données obtenues par la technique d'écoulement à flux bloqué. Ensuite nous représentons les données cinétiques des différentes amines étudiées dans la littérature à partir d'une dépendance en loi puissance en fonction de la concentration. Cette représentation illustre certaines relations structure-propriété et permet de confronter les données expérimentales aux différents mécanismes proposés. Les avantages et limites de chaque mécanisme sont discutés. Finalement nous justifions l'utilisation d'un modèle termoléculaire pour comparer les données obtenues par différents auteurs. Ce modèle conduit à l'observation d'un phénomène de compensation qui est un argument en faveur du mécanisme correspondant.

Abstract — Kinetics of Carbon Dioxide with Amines. I. Stopped-Flow Studies in Aqueous Solutions. A Review — It is possible to find plenty of information about kinetics of reaction between amine and carbone dioxide in the literature. However, there are several experimental techniques and several possible mechanisms which lead to observe sometimes high dispersion of experimental results with various interpretations. A method which enables to compare kinetic constant got by different authors is proposed in this work. First, we present experimental techniques and justify comparison of data obtained by stopped-flow technique. Then, we plot kinetic data for all amines studied in the literature by a power law dependency with the concentration. This representation illustrates some structure-activity relationships and enables to confront experimental results with the different mechanisms. Advantages and limits of each mechanism are discussed. Finally, we justify the choice of the termolecular model to compare data got by different authors. This model leads to a compensation effect which is an argument in favour of this mechanism.

INTRODUCTION

Nowadays carbon dioxide (CO₂) emissions represent over 76% of total emissions of greenhouse gases (Contribution of Working Groups *et al.*, 2008) in terms of CO₂ equivalent. These emissions are mainly due to production of electricity by combustion of fossil hydrocarbons. Amongst other solutions, Post-Combustion Capture (PCC) and storage of CO₂ seems to be an efficient way to reduce greenhouse gases emissions (de Coninck, 2010). Today, efficiency of several PCC processes has been demonstrated at large pilot-plant scale: KS-1 process (Mitsubishi), Chilled Ammonia process (Alstom), MEA based processes (IFPEN-Prosernat, Fluor), etc. Nevertheless, these processes have not been deployed intensively on power plants, mainly due to the cost associated to CO₂ capture with respect to penalties for CO₂ emissions.

Indeed, these processes suffer from a high energy consumption due to the low concentration of CO₂ in the flue gas, that represents the biggest part of the cost associated to CO₂ capture. Thus, in last years, amines with improved thermodynamic performances (Lecomte *et al.*, 2010) or advanced processes (Aleixo *et al.*, 2011; Raynal *et al.*, 2011) have been developed in order to address this issue. As the energy penalty is reduced, investment becomes more and more significant in the cost of CO₂ capture. Thus, more attention should be paid today on kinetics, in order to reduce the height of absorption column that is an important part of the investment. Indeed, the kinetics of the reaction between carbon dioxide and amine affects directly the height of the absorption column. For a given quantity of captured carbon dioxide, the absorption column will be shorter as the reaction is faster (van Loo *et al.*, 2007).

The kinetics of the reaction of CO₂ with different amines has been studied for nearly forty years. During this period methods used by authors have been improved on several aspects: better experimental tools, better mathematical method, more detailed mechanisms etc. On one hand, these improvements allow a better representation of the kinetics of amine-CO₂ system, and thus a better simulation of what happens in an absorption column. On the other hand, results available in the literature cannot be directly compared, because of discrepancies between equipments, experimental conditions and/or models used for data analysis. Thus, it is difficult to infer from these data a good understanding of the influence of the structure of the amine on the kinetics.

The present work describes an original approach which enables to compare data from different authors, in order to get an overview on kinetics of amine-CO₂ systems. First, we justify comparison of results from

different authors on different amines obtained with the stopped-flow technique. In fact, this technique covers a large range of reaction rates and is quite reproducible. Next, we choose to analyze kinetic data obtained by a monoexponential model which is the most widespread method to extract kinetic constant from stopped-flow experiments. Collected data are fitted by a power law dependency of first-order constant with concentration. Influence of *pKa* and steric hindrance on kinetic constants and order are observed and discussed with respect to the different mechanisms proposed in the literature. Nevertheless, we demonstrate that it is impossible to determine an univocal set of kinetic constant associated with the zwitterion mechanism. Single step termolecular mechanism is satisfactory to fit data with only two kinetic constants. A compensation effect is observed between preexponential factor and activation energy of these constants.

1 OVERVIEW OF EXPERIMENTAL TECHNIQUES

Experimental techniques for kinetic measurements on amine-CO₂ systems can be classified in two types of equipment at the laboratory scale: measurement of gas-liquid mass transfer rate on the one hand, and *in situ* measurements of reaction rate after rapid mixing of liquid phases on the other hand. Both types of techniques present advantages and drawbacks for data comparison and the establishment of a structure-activity relationship.

1.1 Mass-Transfer Techniques

Several kinds of gas-liquid reactors are dedicated to measure the kinetics of CO₂ absorption in amine solutions (Laurent *et al.*, 1975). Each of these equipments based on gas-liquid absorption measurement is characterized by a limited range of contact time or liquid mass transfer coefficient, and thus allows measurements in a given concentration range for appropriate formulations of amine. Since reaction rates of amines with CO₂ vary on several orders of magnitude, none of these equipments is adequate for accurate determination of kinetic parameters in the large experimental domain covered by the great variety of amines.

For example, a kinetics of absorption by a 30 wt% monoethanolamine solution will be studied on a wetted-wall column (Puxty *et al.*, 2010), whereas a 50 wt% methyldiethanolamine will be studied on a stirred vessel (Versteeg and van Swaaij, 1988b).

These techniques also imply the use of a mass-transfer model to analyze experimental data. This model takes

into account the thermodynamic equilibrium, the hydrodynamics of gas and liquid phase, physical solubility, diffusion of reactants and products in the liquid phase to fit measured mass transfer rate. In these conditions, estimation of kinetic constants greatly depends on the different hypotheses of the mass transfer model (Danckwerts, 1970; Laurent and Charpentier, 1974; Charpentier, 1981) which can provide additional source of dispersions on data.

For diethanolamine, which is commonly used in gas treatment, Rinker *et al.* (1996) show that dispersion between second order apparent kinetic constants found by different authors is higher than 50%.

1.2 Rapid Mixing Techniques

The most widely used of rapid mixing techniques for CO₂-amine studies is the stopped-flow technique. In comparison with mass-transfer techniques, stopped-flow technique enables to determine kinetic constant usually ranged between about 0.01 and 1 000 s⁻¹, the upper limit corresponding to the inverse of the mixing time which is close to 1 ms. It is then not suited to study kinetics of reaction of fast-reacting amines in industrial conditions. However, kinetic measurements with stopped-flow technique are free from gas-liquid mass transfer limitations. Signal can be directly related to the intrinsic reaction in the liquid phase which makes the method very reproducible. Rayer *et al.* (2011) show that the overall uncertainty on a these data are generally around 5%. Then this method is well fitted to draw quantitative structure activity relationship from the comparison of intrinsic kinetics of reaction of very different amines with CO₂.

1.3 Scope of This Work

This review intends to compile experimental data obtained with the stopped-flow technique.

Different methods are available to treat raw data from this technique, which depend on detection type (conductimetry, spectrophotometry, etc.), mechanistic hypotheses and operating condition. For our purpose, we shall choose a common method to compare kinetic constants of amine studied by different authors.

2 DATA TREATMENT OF STOPPED-FLOW DATA

We distinguish two methods to derive kinetic parameters from stopped-flow data: numerical model on the one hand and analytical model on the other hand. We consider advantages and drawbacks of both methods to select the most adapted to our purpose.

2.1 Numerical Models

Numerical models take into account all chemical species with the reactions and thermodynamic equilibria in which they are involved. Kinetic parameters are optimized to reduce deviation between the model and experimental data. This kind of models is necessary when spectrophotometric detection is used to follow the reaction (Barth *et al.*, 1981, 1983, 1984, 1986) or if operating conditions like CO₂ loading is not compatible with an analytical solution of the model (Conway *et al.*, 2011, 2012; McCann *et al.*, 2009, 2011; Wang *et al.*, 2011; Xiang *et al.*, 2012).

Although these methods are quite exhaustive, results on kinetic constants are still dependant on mechanistic hypotheses or thermodynamic model for non ideal solutions.

2.2 Analytical Model

Analytical model is the most widespread approach for stopped-flow studies on amine-CO₂ reaction. This approach considers a single, irreversible reaction with amine in large excess, of first order with respect to CO₂. Generally, authors operate with a total concentration of amine at least ten times higher than the concentration of carbon dioxide. In these conditions, the variation of concentration of chemical species depends on the pseudo first order kinetic constant k_0 according to a monoexponential variation. For conductivity stopped flow measurements, the variation of concentrations of ionic species is monitored by the change of conductance in the solution. Conductance G (S) is the inverse of the electric resistance R (Ω), A (S) is the amplitude of the signal, k_0 the pseudo first order kinetic constant, t (s) is the time and C (S) is the value of the conductance at the end of the observed reaction. Variation of conductance is then related to formation of amine salts and to k_0 according Equation (1) (Ali *et al.*, 2000):

$$\frac{1}{R(t)} = G(t) = -A \times \exp(-k_0 \times t) + C \quad (1)$$

The pseudo first order kinetic constant k_0 is defined as shown by Equation (2). When it is measured in a large excess of amine, k_0 depends on the nature of the amine, the concentration of amine and the temperature. For the rest of the article, we decided to use k_0 values because they directly come from stopped-flow raw data which are quite reproducible. Then, we limit our work to compare first order kinetic constant obtained by this analytical method:

$$r_{\text{CO}_2} = k_0 \cdot [\text{CO}_2] \quad (2)$$

3 SYNTHESIS OF KINETIC DATA

3.1 Representation of the Raw Data

All pseudo-first order constants k_0 determined with a stopped-flow apparatus with a conductimetric detection and available in the literature have been compiled. The studied amines and the corresponding references are listed in Table 1. Some amines have been studied by different authors and, apart from two cases (Ali *et al.*, 2010) for molecule No. 8 (methylethanolamine), and (Crooks and Donnellan, 1989) for molecule No. 18 (diethanolamine), a discrepancy smaller than 25% between kinetic constants is observed. After elimination of the two latter references, we retain for each amine the study that covers the largest range of amine concentration and where data are available at 25°C. Corresponding references have been represented in bold in Table 1.

In order to analyze these raw data, without any mechanistic assumption, we determine the two parameters k_{Am} and n of the power law model given by Equation (3) by fitting variation of experimental pseudo first order constant k_0 as a function of concentration for each amine. k_{Am} is an empirical kinetic constant and n is the apparent order of reaction with respect to amine. The average relative deviation between the experimental constants and this model over all data is 7.3%. For each amine, parameters k_{Am} and n are plotted in Figure 1. We also represent by continuous lines values of (k_{Am}, n) giving the same value of k_0 for concentration of amine of 100 mol.m^{-3} . This concentration has been chosen because all studied amines can be evaluated at this concentration (1 wt% for molar weight of 100 g.mol^{-1} and a density of 10^6 g.m^{-3}) in the operating range available by the stopped-flow technique:

$$k_0 = k_{Am} \cdot [Am]^n \quad (3)$$

3.2 Analysis of the Raw Data

Values of k_{Am} and n plotted in Figure 1 are reported in Table 2 with the average relative deviation between the model and the experimental data. Apparent order n with respect to amine is between 0.6 and 2.0.

Most of tertiary amines, represented by triangles in Figure 1, have an apparent global order of reaction close to 1 with respect to amine. For molecules 5, 6 and 11, we observe an apparent order lower than 1. A linear fit (order = 1) will in fact lead to an intercept which is significantly different from zero, showing evidence of another reaction being preponderant in diluted solutions which shows increasing rate with pK_a . We can force order of these molecules at 1 as it is done by most of authors. From this point, we only consider values of

k_{Am} obtained from fitting with $n = 1$ for tertiary amines. Corresponding values of the empirical kinetics constant k_{Am} are between 3×10^{-3} and $10^{-1} \text{ m}^3.\text{mol}^{-1}.\text{s}^{-1}$ and increase with the value of pK_a of the tertiary amine.

Primary and secondary amines, represented by circles have a global order of reaction included between 1 and 2 with respect to amine. Several observations can be drawn from these data.

Series of monoamines No. 7 to 11 correspond to ethanolamines $\text{R-NH-CH}_2\text{-CH}_2\text{-OH}$ with R being with increasing number: hydrogen (7), methyl (8), ethyl (9), *n*-butyl (10) and tert-butyl (11). For this series of molecules, the pK_a varies between 9.44 and 10.12 with an increasing steric hindrance around the nitrogen group. This variation of pK_a and steric hindrance is correlated with significant variations of k_{Am} and n . It is very interesting to notice that the effect of hindrance around the amino group on the order n is not monotone: starting from 1.2 with MEA, it first increases up to a maximum around 2 for ethylethanolamine, and then decreases down to a value of 1 for tert-butylethanolamine. It is also possible to compare k_0 for this amine at a concentration of 100 mol.m^{-3} : we see first an increase of the reaction rate from MEA to methylethanolamine, and an increasing negative effect of hindrance on k_0 as the alkyl substituent of the secondary amine gets longer or more substituted, as k_0 decreases by two orders of magnitude between methylethanolamine and tert-butylethanolamine.

Another result that needs to be pointed out, is the fact that all molecules having an amino group linked to a quaternary carbon (No. 11 to 14) have a value of order n less than 1.2. For these molecules, reaction rates figured by k_0 are intermediate between tertiary amine on one hand and moderately hindered primary and secondary amines on the other hand. For example, tert-butylethanolamine (11), that can be fitted with $n = 1$, has a 2.3 time higher value of k_{Am} compared to the fastest tertiary amine (6). This difference is likely explained by the higher pK_a of tert-butylethanolamine. According to Ali *et al.* (2002), this amine fits the description given by Sartori and Savage (1983) of a severely sterically hindered amine. These authors have suggested that such amines are unable to form a carbamate and then behave as tertiary amine. If we now have a closer look on the series of molecules 12 to 14, which are all primary amine with an amino group linked to a quaternary carbon and exhibit an order n of 1.2, an increase of the pK_a tends to increase the value of k_{Am} , as it has been already pointed out with tertiary amine. However, these sterically hindered primary amines are faster to react with CO_2 than tertiary amines having same pK_a , as can be seen by comparing (6) with (12) ($pK_a = 9.72\text{--}9.75$) or (13) with (5) ($pK_a = 9.48\text{--}9.50$).

TABLE 1

Name, chemical structure, references of stopped-flow kinetic studies of amine-CO₂ reaction with conductimetric detection, concentration range, temperature range, *pKa* at 25 °C and references of *pKa* values. References selected for determination of (*k_{Am}*, *n*) parameters at 25°C are indicated in bold

Name	Number	Chemical structure	Authors	Concentration range (mol.m ⁻³)	Temperature range (°C)	<i>pKa</i> at 25°C	References
Triethanolamine	1		Crooks and Donnellan (1990)	25-176	25	7.76	da Silva and Svendsen (2007)
Methyldiethanolamine	2		Crooks and Donnellan (1990)	25-176	25	8.52	da Silva and Svendsen (2007)
Dimethylmonoethanolamine	3		Henni et al. (2008)	303-986	25-40	9.23	da Silva and Svendsen (2007)
3-Dimethylamino-1-propanol	4		Kadiwala et al. (2012)	350-1 003	25-40	9.54	Kadiwala et al. (2012)
1-Dimethylamino-2-propanol	5		Kadiwala et al. (2012)	238-1 000	25-40	9.50	Kadiwala et al. (2012)
Diethylmonoethanolamine	6		Li et al. (2007)	197-997	25-40	9.75	da Silva and Svendsen (2007)
Monoethanolamine	7		Crooks and Donnellan (1989) Alper (1990b) Ali et al. (2002)	20-59 28-52 (at 25°C) 5-36	25 5-40 25-40	9.44	Hamborg and Versteeg (2009)
Methylethanolamine	8		Ali et al. (2002) Ali et al. (2010) Bavbek and Alper (1999)	8-39 20-69 25-50	10-35 25-40 30	9.85	Hamborg and Versteeg (2009)
Ethylethanolamine	9		Li et al. (2007) Bavbek and Alper (1999)	28-82 25-50	25-40 30	9.89	Chemicalize (2012a)
<i>n</i> -Butylethanolamine	10		Ali et al. (2002)	20-98	10-35	10.00	Chemicalize (2012b)
Tert-Butylethanolamine	11		Ali et al. (2002)	17-63	10-35	10.12	Littel et al., (1990b)
2-amino-2-methyl-1-propanol	12		Alper (1990b) Ali (2005)	25-1 486 (at 25°C) 54-346	5-25 25-40	9.72	da Silva and Svendsen (2007)

(continued)

TABLE 1 (continued)

Name	Number	Chemical structure	Authors	Concentration range (mol.m ⁻³)	Temperature range (°C)	pKa at 25°C	References
2-amino-2-methylpropan-1,3-diol	13		Bouhamra et al. (1999)	25-1 351 (at 25°C)	5-30	9.48	Chemicalize (2012b)
2-amino-2-hydroxymethyl-1,3-propanediol	14		Ume and Alper (2012)	500-2 000	25	8.95	Chemicalize (2012d)
1-amino-2-propanol	15		Henni et al. (2008) Bavbek and Alper (1999)	25-82 25-50	25-40 30	9.46	da Silva and Svendsen (2007)
3-amino-1-propanol	16		Henni et al. (2008) Bavbek and Alper (1999)	27-61 25-50	25-40 30	10.0	da Silva and Svendsen (2007)
2-(2-aminoethoxy)ethanol	17		Alper (1990a)	12-206 (at 25°C)	5-25	9.46	da Silva and Svendsen (2007)
Diethanolamine	18		Crooks and Donnellan (1989) Ali (2004) Li et al. (2007)	100-1 016 66-519 150-518	25 25-40 25-40	8.96	da Silva and Svendsen (2007)
Morpholine	19		Alper (1990a) Ali et al. (2010)	3-102 (at 25°C) 32-130	5-25 25-40	8.49	da Silva and Svendsen (2007)
Ethylenediamine	20		Li et al. (2007) Rayer et al. (2011)	26-68 20-101	25-40 25-40	9.92	da Silva and Svendsen (2007)
Piperazine	21		Gordesli and Alper (2011)	10-100 (at 25°C)	5-25	9.71-5.41	Hamborg and Versteeg (2009)
Hydroxyethylpiperazine	22		Ume et al. (2012)	2.5-30	25	8.92-3.97	Hamborg and Versteeg (2009)

Figure 1

Values of k_{Am} , n obtained from references in bold of Table 1. Plot of (k_{Am}, n) according to $k_0 = k_{Am}[Am]^n$ for tertiary amines ($\blacktriangle$), primary and secondary amines ($\bullet$) listed in Table 1. Continuous lines represent values of (k_{Am}, n) giving the same value of k_0 for $[Am] = 100 \text{ mol.m}^{-3}$. Setting $n = 1$ for molecules 5, 6 and 11 gives 5', 6', 11'.

Finally, molecules 18 and 19 can be compared. These molecules are both secondary amines with the same number of carbon between nitrogen and the oxygen atoms. Linear diethanolamine (18) reacts 10 times more slowly than cyclic morpholine (19) at 100 mol.m^{-3} inspite of the fact that DEA is more basic.

Unfortunately, not enough multiamines have been tested in the literature to draw conclusions. We can just point out that molecule 20, 21 and 22 are the ones that exhibit the fastest kinetics.

Explanations of observed behaviors may be found in the different mechanisms proposed in the literature for tertiary amines on one hand, for primary and secondary amine on the other hand.

4 TERTIARY AMINES

4.1 Mechanism Proposed in Literature

Absorption of CO_2 in aqueous amine solutions implies two sets of reaction. The first set of reactions involves carbon dioxide with water or hydroxide ions and is common to all amines. The second set of reactions for tertiary amine is distinct from primary and secondary

amines, the latter forming carbamates. We limit here to reactions of CO_2 with large excess of amine, without taking into account reversibility.

4.1.1 Common Pathway

Carbon dioxide in presence of water is hydrated and forms carbonic acid (4). Carbonic acid reacts with a basic compound (B) present in solution (5). The base can be an amine, water or an hydroxide ion. Pinsent *et al.* (1956) showed first that reaction (4) is the limiting step and determined the pseudo-first-order associated rate constant (at 25°C $k'_{\text{H}_2\text{O}} = 2.57 \times 10^{-2} \text{ s}^{-1}$). More recently Soli and Byrne (2002) determined the rate of this reaction (at 25°C $k'_{\text{H}_2\text{O}} = 3.06 \times 10^{-2} \text{ s}^{-1}$). These values are not identical but have the same order of magnitude. They show that this reaction is very slow in front of hydroxyde- CO_2 and amine- CO_2 reaction described below. The rate of reaction of carbon dioxide according to hydration mechanism is shown by Equation (6):

$$r_{\text{CO}_2}^{\text{H}_2\text{O}} = \underbrace{k_{\text{H}_2\text{O}}[\text{H}_2\text{O}]}_{k'_{\text{H}_2\text{O}}} \cdot [\text{CO}_2] \quad (6)$$

In aqueous basic solution, carbon dioxide reacts with an hydroxide ion to form a bicarbonate ion (7). Rate of this reaction is given by kinetic law (8). The correlation determined by Pinsent *et al.* (1956) gives $k_{\text{HO}^-} = 8.32 \text{ m}^3.\text{mol}^{-1}.\text{s}^{-1}$ at 25°C :

$$r_{\text{CO}_2}^{\text{HO}^-} = k_{\text{HO}^-} \cdot [\text{CO}_2] \cdot [\text{HO}^-] \quad (8)$$

4.1.2 Tertiary Amine Mechanisms

Donaldson and Nguyen (1980) show that tertiary amines (R_3N) do not react directly with carbon dioxide. Tertiary amines are used as “pseudo-catalyst”. They accelerate the reaction of hydration of carbon dioxide. For this reason, this mechanism is called based-catalyzed hydration mechanism (9). Since concentration of water does not vary too much in kinetic studies and is in large excess, this reaction is generally considered to be first order with respect to amine concentration (10) with the pseudo-constant $k'_{\text{R}_3\text{N}} = k_{\text{R}_3\text{N}} \cdot [\text{H}_2\text{O}]$ (Crooks and Donnellan, 1990):

TABLE 2

Chemical structure, number, value of k_{Am} and n for selected data with average relative deviation between model and experimental data on concentration range specified in Table 1

Chemical structure	Number	k_{Am} ($\text{m}^{3n} \cdot \text{mol}^{-n} \cdot \text{s}^{-1}$)	n	Average relative error (%)
1	1.66×10^{-3}	0.99	0.4
2	3.20×10^{-3}	0.99	3.3
3	2.64×10^{-2}	1.01	2.4
4	3.29×10^{-2}	0.99	12.1
5	1.06×10^{-1}	0.76	3.6
	5'	2.17×10^{-2}	1.00	7.3
6	1.58×10^{-1}	0.89	3.3
	6'	7.58×10^{-2}	1.00	5.9
7	2.42×10^0	1.16	5.4
8	6.54×10^{-1}	1.71	3.6
9	4.76×10^{-2}	1.95	7.9
10	3.17×10^{-1}	1.43	3.3
11	9.54×10^{-1}	0.57	12.6
	11'	1.83×10^{-1}	1.00	20.6
12	1.84×10^{-1}	1.15	5.9
13	3.31×10^{-2}	1.21	8.3
14	7.54×10^{-3}	1.22	5.0
15	9.29×10^{-1}	1.31	3.7
16	2.15×10^0	1.18	2.1
17	2.25×10^0	1.14	7.6
18	8.96×10^{-3}	1.62	2.9
19	2.78×10^0	1.14	7.7

(continued)

TABLE 2 (continued)

Chemical structure	Number	k_{Am} ($m^{3n} \cdot mol^{-n} \cdot s^{-1}$)	n	Average relative error (%)
20	5.95×10^0	1.14	5.5
21	4.30×10^0	1.41	7.2
22	2.84×10^0	1.41	30.9

$$r_{CO_2}^{R_3N} = \underbrace{k_{R_3N} \cdot [H_2O]}_{k'_{R_3N}} \cdot [CO_2] \cdot [R_3N] \quad (10)$$

A two-step mechanism was also suggested by Yu *et al.* (1985). Carbon dioxide reacts first with the amine to form a zwitterion (11). The zwitterion is then hydrolyzed by water to form ammonium ions and bicarbonate ions (12). As a very instable intermediate, the zwitterion is assumed at a steady state low concentration. With this assumption, reaction rate of CO_2 is shown in Equation (13):

$$r_{CO_2}^{R_3N} = \frac{[R_3N] \cdot [CO_2]}{\frac{1}{k_{NA}} + \frac{1}{k_{Hy}^{H_2O}}} = k'_{R_3N} [R_3N] \cdot [CO_2] \quad (13)$$

$$\text{with } \frac{1}{k'_{R_3N}} = \frac{1}{k_{NA}} + \frac{1}{k_{Hy}^{H_2O}} \text{ and } k_{Hy}^{H_2O} = \frac{k_{NA} \cdot k_{Hy}^{H_2O} [H_2O]}{k_{-NA}}$$

In the case of tertiary amines, the overall rate of reaction of carbon dioxide (Eq. 14) corresponds to the sum of the contributions of three reaction paths (4 + 5), (7), and the reaction with the tertiary amine (9) or (11 + 12). Based-catalyzed hydration mechanism or zwitterion mechanism both yield to an order of reaction of one with respect to amine:

$$r_{CO_2}^{III} = r_{CO_2}^{H_2O} + r_{CO_2}^{HO^-} + r_{CO_2}^{R_3N} \quad (14)$$

4.2 Confrontation with Experimental Data

Based catalyzed hydration mechanism and zwitterion mechanism are both first order mechanisms with respect to amine. Both mechanisms can then explain experimental results of Figure 1, considering that reaction of CO_2 with water and HO^- is neglected.

We focus our discussion on the six tertiary amines presented in Tables 1 and 2. In these tables, we indicate results of pKa at 25°C determined by da Silva and Svendsen (2007) and Kadiwala *et al.* (2012) for these

Figure 2

Kinetic constant k'_{R_3N} values versus pKa .

$$k'_{R_3N} = 6.22 \times 10^{-10} \cdot \exp(1.87 \times pKa) \text{ and } R^2 = 0.93.$$

amines. Since kinetics of tertiary amine- CO_2 shows a partial order of 1 with respect to amine, k_{Am} is identified to k'_{R_3N} .

We plot in Figure 2 values of k'_{R_3N} as a function of pKa . We outline, as suggested by Littell *et al.* (1990a) that the logarithm of the second order kinetic constant of amine- CO_2 reaction shows a quasi linear variation with the of pKa of the amine according to a Brønsted relationship.

5 PRIMARY AND SECONDARY AMINES

5.1 Mechanisms Proposed in Literature

Primary and secondary amines generally react with CO_2 to form carbamates. As we limit our discussion to reactions of CO_2 with large excess of amine, we do not take into account inverse reactions or hydrolysis of carbamate to carbonates.

The two-step mechanism proceeding through the formation of a zwitterion as an intermediate has been suggested for the first time by [Caplow \(1968\)](#) and reintroduced by [Danckwerts \(1979\)](#). In the first step, amine reacts with carbon dioxide and forms a zwitterion (15). Then zwitterion is deprotonated by a base B (16). In these equations, k_{NA} corresponds to the kinetic constant of the nucleophilic addition, k_{-NA} corresponds to the kinetic constant of the reverse reaction and k_{Dep}^B corresponds to the kinetic constant of the deprotonation of the zwitterion by a base B:

Versteeg and van Swaaij (1988a) have shown that deprotonation reaction with hydroxide ion as a base is insignificant for unloaded solution. Only amine and water have to be considered as bases for deprotonation of the zwitterion. The rate of the reaction of CO_2 with amine is then given by Equation (17), assuming zwitterion concentration at quasi steady state ([Danckwerts, 1979](#)). We simplify this equation as shown by Equation (18) and with $k_{Dep}^{R_2NH}$ and $k_{Dep}^{H_2O}$ defined in Equation (19):

$$r_{CO_2}^{R_2NH} = \frac{[R_2NH] \cdot [CO_2]}{\frac{1}{k_{NA}} + \frac{k_{-NA}}{k_{NA}(k_{Dep}^{R_2NH} \cdot [R_2NH] + k_{Dep}^{H_2O} \cdot [H_2O])}} \quad (17)$$

$$r_{CO_2}^{R_2NH} = \frac{[R_2NH] \cdot [CO_2]}{\frac{1}{k_{NA}} + \frac{1}{k_{Dep}^{R_2NH} \cdot [R_2NH] + k_{Dep}^{H_2O} \cdot [H_2O]}} \quad (18)$$

$$k_{Dep}^{R_2NH} = \frac{k_{NA} \cdot k_{Dep}^{R_2NH}}{k_{-NA}}; k_{Dep}^{H_2O} = \frac{k_{NA} \cdot k_{Dep}^{H_2O}}{k_{-NA}} \quad (19)$$

Recently [McCann *et al.* \(2009\)](#) proposed a mechanism which is close to the zwitterion model. According to them, the reaction between carbon dioxide and amine forms a carbamic acid (20). Carbamic acid is a more stable tautomeric form of the zwitterion according to NMR measurements. Then carbamic acid is deprotonated instantaneously by a base (21). Reaction rate according to this carbamic acid mechanism is given by Equation (22) which has the same expression as the limit case of zwitterion model when nucleophilic addition is the rate-limiting step:

$$r_{CO_2}^{R_2NH} = k_{NA} \cdot [R_2NH] \cdot [CO_2] \quad (22)$$

Another mechanism which considers that carbon dioxide, amine and base react simultaneously, has been suggested by [Crooks and Donnellan \(1989\)](#). This termolecular mechanism (23) corresponds to a limiting case of the zwitterion mechanism where the limiting step is deprotonation. This mechanism has been recently supported by molecular modelisation ([da Silva and Svendsen, 2004](#)). In this work, [da Silva and Svendsen \(2004\)](#) show that energetic levels are in favour of a one step mechanism. In this equation, k_{ter}^B corresponds to the third order kinetic constant of the termolecular mechanism. By analogy with the zwitterion mechanism, termolecular reaction with hydroxide ions is insignificant. The reaction rate according to this termolecular mechanism is given by Equation (24). Third order kinetic constants $k_{ter}^{H_2O}$ and $k_{ter}^{R_2NH}$ correspond to the reaction of CO_2 with respectively one molecule of amine and one molecule of water and two molecules of amine. The overall rate of carbon dioxide reaction for a primary or secondary amine is then given in Equation (25):

$$r_{CO_2}^{R_2NH} = k_{ter}^{H_2O} \cdot [H_2O] \cdot [R_2NH] \cdot [CO_2] + k_{ter}^{R_2NH} [R_2NH]^2 \cdot [CO_2] \quad (24)$$

$$r_{CO_2}^{I/II} = r_{CO_2}^{H_2O} + r_{CO_2}^{HO^-} + r_{CO_2}^{R_2NH} \quad (25)$$

5.2 Confrontation of Mechanisms with Experimental Data

The series of ethanolamines 7, 8, 9, 10 and 11 with increasing molecular weight and hindrance of substituting group on nitrogen, respectively hydrogen, methyl, ethyl, *n*-butyl and tert-butyl is represented by [Figure 3](#). These molecules are in a *pKa* range between 9.44 for monoethanolamine (7) ([Hamborg and Versteeg, 2009](#)) and 10.12 for *t*-butyl-ethanolamine (11) ([Littel *et al.*, 1990b](#)) at 25°C. Values of *pKa* and *Taft* constants which give an indication of steric hindrance have been indicated in [Table 3](#). Evolution of apparent order *n* with these parameters is a first trial for the three different mechanisms.

5.2.1 Carbamic Acid Mechanism

[McCann *et al.* \(2009\)](#) use the mechanism of carbamic acid to explain kinetics of monoethanolamine in loaded solution. Although it is convenient to account for first

Figure 3

Values of (k_{Am}, n) ethanolamines (No. 7, 8, 9, 10 and 11) at 25°C. We indicate iso- k_0 lines for a concentration of amine of 100 mol.m⁻³.

order kinetics with respect to amine, it can not be generalized to orders larger than 1.

5.2.2 Zwitterion Mechanism

For monoethanolamine (7), apparent order with respect to amine n is close to 1, which matches either with the nucleophilic addition or the deprotonation by water as the limiting step of the carbamate formation. Iida and Sato (2012) suggest that nucleophilic addition of zwitterion mechanism is the rate-limiting step. However, Kumar *et al.* (2003) assume that deprotonation by water is the limiting step at low concentration of amine. Since monoethanolamine is not sterically hindered, it seems

yet difficult to consider a deprotonation as a limiting step. Indeed, deprotonations reactions, which are acid-base reactions, are generally easier than nucleophilic addition, hydration or hydrolysis reaction. For example, at 25°C the rate constant of the reaction between oxonium ions and hydroxide ions in water is equal to 1.4×10^{11} dm³.mol⁻¹.s⁻¹ (Atkins and de Paula, 2006).

With a methyl group on the nitrogen, methylethanolamine (8) is slightly more basic and moderately hindered. Apparent order n is close to 1.7. Consistently with the discussion on the monoethanolamine, this intermediate order for methylethanolamine (8) can be explained by a competition between nucleophilic addition step and deprotonation of zwitterion by the amine. With an ethyl group as a substituent (9), apparent order n is almost 2 consistent with a deprotonation of the zwitterion by the amine as the rate limiting step in the studied range of concentration.

With a *n*-butyl substituent to the nitrogen atom (10), n is close to 1.4 with a value of k_0 10 times less than methylethanolamine (8) at the same concentration of 100 mol.m⁻³. Two hypotheses can support this result. We either have a competition between nucleophilic addition step and deprotonation by amine or a competition between deprotonation by water and deprotonation by amine.

Further increase of steric hindrance for molecule 11 leads to an apparent order of 1. Instead of deprotonation, zwitterion reacts directly with water to form bicarbonate. It is yet not possible to assess which step is rate-limiting in this case. This mechanism has also been suggested by Yu *et al.* (1985) for tertiary amine as an alternative to the base-catalyzed hydration mechanism. Indeed, this molecule follows the Brønsted relationship observed in Figure 2 and then behaves as tertiary amines.

It comes out that the zwitterion mechanism can explain apparent orders between 1 and 2 observed for primary and secondary amine which are consistent with steric hindrance of the nitrogen. However, in most cases,

TABLE 3
Values of pK_a at 25°C and Taft constants for the series of molecule No. 7 to 11 (Taft (1976)).

Number	Chemical structure	pK_a	References	Taft constant
7	Hydrogene	9.44	Hamborg and Versteeg (2009)	0
8	Methyl	9.85	Hamborg and Versteeg (2009)	-1.24
9	Ethyl	9.89	Chemicalize (2012a)	-1.31
10	<i>n</i> -Butyl	10.00	Chemicalize (2012b)	-1.63
11	Tert-butyl	10.12	Littel <i>et al.</i> (1990b)	-2.78

uncertainty remains on the respective contribution of the two steps of the reaction.

5.2.3 Termolecular Mechanism

Crooks and Donnellan (1989) explain reaction of monoethanolamine (7) with CO₂ by a single step termolecular mechanism involving amine, water and CO₂ where nucleophilic addition and deprotonation represent one single energy barrier. This hypothesis has been supported by *ab initio* calculations of da Silva and Svendsen (2004).

According to termolecular mechanism, the apparent order of 1.7 for methylethanolamine (8) is explained by a competition between reaction of CO₂ with amine and water (order 1) and with two molecules of amine (order 2).

For ethylethanolamine (9), order of 2 means that the one step reaction of CO₂ with amine and water is negligible in front of one step reaction of CO₂ with two molecules of amine.

Apparent order of 1.4 for *n*-butyl-ethanolamine (10) is explained by the competition between the two single step termolecular reactions as for methylethanolamine (8).

Order 1 for tert-butylethanolamine (11), which does not form carbamate, can be explained by the base-catalyzed hydration mechanism of tertiary amine, which can be seen as an extension of termolecular mechanism for tertiary amine and severely hindered secondary amines.

To conclude with this series of primary and secondary amines, one-step termolecular or zwitterion mechanisms both explain experimental orders of reaction. One-step termolecular mechanism leads to the same kinetic law as the zwitterion mechanism where the deprotonation step is rate limiting.

On a practical point of view, the choice of one or the other mechanism should be driven by the ability of the model to fit experimental data of k_0 on the studied concentration range and to determine all its kinetic constants.

5.3 Indetermination of the Zwitterion Model

For primary and secondary amines, the set of experimental data does not allow to extract the three kinetic constants of the zwitterion model. This indetermination is due to the small variation of concentration of water.

For example in the case of 2-amino-2-methyl-1-propanol studied by Alper (1990b), the concentration of amine varies between 25 and 1 486 mol.m⁻³, correlated with variation of water concentration between 55 431 and 48 197 mol.m⁻³ according to the Equation (26)

where ρ_w is the density of water, M_{Am} is the molecular weight of amine and M_w is the molecular weight of water:

$$[H_2O] = \frac{\rho_w - [Am] \times M_{Am}}{M_w} \quad (26)$$

As the concentration of amine varies more than 60 times, the concentration of water varies only by 15 percent. In order to discriminate contributions of k_{NA} , $k_{Dep}^{R_2NH}$ and $k_{Dep}^{H_2O}$, both concentrations of water and amine should vary significantly. Since it is not the case, several sets of kinetic constants can fit variation of k_0 with amine concentration. This is illustrated by the case of piperazine for which experimental results obtained by Rayer *et al.* (2011) at 30°C are given in Table 4.

With these data we calculate with Maple® the response surface of k_{NA} , $k_{Dep}^{R_2NH}$ and $k_{Dep}^{H_2O}$ yielding to an average relative deviation below 1% between the model and experimental values of k_0 . This response surface has been obtained for values of constant between 10⁻⁵ and 10⁵ using 200 points for each constant on a logarithmic scale. Red points which appear in Figure 4, correspond to values of k_{NA} , $k_{Dep}^{R_2NH}$ and $k_{Dep}^{H_2O}$ that give a prediction of k_0 with an average relative deviation from the experimental data lower than 1%.

From this calculation, it is impossible to minimize the average relative deviation giving a single set of kinetic parameters able to represent the reaction of piperazine with CO₂. In this case, the response surface of those parameters giving an average relative deviation below 1% stretches between 10^{1.3} and 10^{2.8} m³.mol⁻¹.s⁻¹ for k_{NA} , between 10^{-1.6} and 10^{0.4} m⁶.mol⁻².s⁻¹ for $k_{Dep}^{R_2NH}$ and between 10^{-4.1} and 10^{-3.1} m⁶.mol⁻².s⁻¹ for $k_{Dep}^{H_2O}$.

In this surface, we identify two areas. The first with low value of k_{NA} (10^{1.3} m³.mol⁻¹.s⁻¹) and high value of $k_{Dep}^{R_2NH}$ (10^{0.4} m⁶.mol⁻².s⁻¹) corresponds to the

TABLE 4
Experimental data of k_0 for piperazine determined by Rayer *et al.* (2011) at 30°C

[PZ] (mol.m ⁻³)	[H ₂ O] (mol.m ⁻³)	k_0 (s ⁻¹)
20	55 460	341
31	55 409	533
40	55 365	711
52	55 308	939
60	55 270	1 100
80	55 174	1 497
100	55 077	1 910

Figure 4

Response surface for average relative error below 1% for k_0 modelled with zwitterion mechanism for piperazine at 30°C (Rayer *et al.*, 2011). Variation between $10^{1.3}$ and $10^{2.8}$ $\text{m}^3\cdot\text{mol}^{-1}\cdot\text{s}^{-1}$ for k_{NA} , between $10^{-1.6}$ and $10^{0.4}$ $\text{m}^6\cdot\text{mol}^{-2}\cdot\text{s}^{-1}$ for $k_{\text{Dep}}^{\text{R}_2\text{NH}}$ and between $10^{-4.1}$ and $10^{-3.1}$ $\text{m}^6\cdot\text{mol}^{-2}\cdot\text{s}^{-1}$ for $k_{\text{Dep}}^{\text{H}_2\text{O}}$.

nucleophilic addition limiting step. In this area, value variation of $k_{\text{Dep}}^{\text{H}_2\text{O}}$ by a factor of 10 is not sensitive on the result. The second one with an intermediate value of $k_{\text{Dep}}^{\text{H}_2\text{O}}$ ($10^{-3.5}$ $\text{m}^6\cdot\text{mol}^{-2}\cdot\text{s}^{-1}$) and a low value of $k_{\text{Dep}}^{\text{R}_2\text{NH}}$ ($10^{-1.6}$ $\text{m}^6\cdot\text{mol}^{-2}\cdot\text{s}^{-1}$) corresponds to the deprotonation by water limiting step. In this area, variation of k_{NA} by a factor close to 10 has no impact on k_0 .

Finally, it is impossible to determine what is the limiting step of the zwitterion mechanism. We reach the same conclusion for 2-amino-2-methyl-1-propanol with $n = 1$ (Alper, 1990b). In the case of a study of an amine with $n = 2$, (ethylethanolamine (Li *et al.*, 2007)), kinetic constant $k_{\text{Dep}}^{\text{R}_2\text{NH}}$ can be determined but other constants are insensitive as they are first order kinetic constant according to the amine concentration.

In overall, it is mathematically impossible to determine a unique set of kinetic constants related to the zwitterion model which would be characteristic of a given amine.

5.4 Mathematical Expression of the Termolecular Mechanism

With apparent order n between one and two, all data can be fitted by the termolecular mechanism given by Equation (27). For practical reasons, we replace $k_{\text{ter}}^{\text{H}_2\text{O}}$ by k_1 and $k_{\text{ter}}^{\text{R}_2\text{NH}}$ by k_2 and obtain Equation (28). Unlike the variety of interpretations associated to the zwitterion model, the fitting of k_0 with the termolecular model

yields to one single set of (k_1 ; k_2) parameters to characterize each amine, independently of its structure and functionality (primary, secondary or tertiary):

$$k_0 = k_{\text{ter}}^{\text{H}_2\text{O}} \cdot [\text{H}_2\text{O}] \cdot [\text{R}_2\text{NH}] + k_{\text{ter}}^{\text{R}_2\text{NH}} [\text{R}_2\text{NH}]^2 \quad (27)$$

$$k_0 = k_1 \cdot [\text{H}_2\text{O}] \cdot [\text{R}_2\text{NH}] + k_2 \cdot [\text{R}_2\text{NH}]^2 \quad (28)$$

6 COMPENSATION EFFECT

Based on experimental data collected in Table 1, we determine parameters k_1 and k_2 of the Equation (28). Values of k_1 and k_2 at different temperatures are reported in Table 5 with average relative error between model and experimental values of k_0 . Deprotonation by amine is not considered ($k_2 = 0$) for amines with $n = 1$ (molecule 3, 4, 5, 6, 11) and deprotonation by water is not considered ($k_1 = 0$) for amines with $n = 2$ (molecule 9).

Then, we determine parameters of Arrhenius law for k_1 , k_2 constants given by Equation (29) and (30). Figures 5 and 6 show the activation energy E_a of each kinetic constant k_1 and k_2 versus $\ln(A)$. For both constants, we can draw a linear relationship between activation energy and reaction frequency factor A as shown in Equation (31).

$$k_1 = A_1 \cdot \exp\left(\frac{-E_{a1}}{RT}\right) \quad (29)$$

$$k_2 = A_2 \cdot \exp\left(\frac{-E_{a2}}{RT}\right) \quad (30)$$

$$E_{ai} = b \cdot \ln A_i + c \quad (31)$$

This correlation has been described in the literature as a compensation effect. According to Liu and Guo (2001), this phenomenon appears in several fields of chemistry (adsorption, chromatography, substitution reaction, proton transfer, etc.). According to Liu and Guo (2001), there are two main explanations to this phenomenon.

6.1 Statistical Compensation Effect

In the temperature range of the stopped-flow experiments, the neperian logarithm of the kinetic constant ($\ln k_1$ and $\ln k_2$) and the value of $1/T$ have a limited variation which can account for uncertainty on the independent determination of preexponential factor and energy of activation. This indetermination can be a first explanation for the apparent compensation effect generally

TABLE 5
Number, value of k_1 and k_2 and average relative deviation between termolecular model and experimental values of k_0
from literature data specified in Table 1

Number	Temperature (°C)	k_1 (m ⁶ .mol ⁻² .s ⁻¹)	k_2 (m ⁶ .mol ⁻² .s ⁻¹)	Average relative error (%)
3	25	5.27×10^{-7}	-	2.5
	30	7.49×10^{-7}	-	2.2
	35	1.03×10^{-6}	-	3.7
	40	1.47×10^{-6}	-	3.7
4	25	6.01×10^{-7}	-	12.0
	30	1.06×10^{-6}	-	11.3
	35	1.74×10^{-6}	-	6.1
	40	2.64×10^{-6}	-	7.6
5	25	4.22×10^{-7}	-	5.8
	30	6.19×10^{-7}	-	7.6
	35	9.54×10^{-7}	-	4.7
	40	1.40×10^{-6}	-	5.6
6	25	1.48×10^{-6}	-	3.7
	30	2.10×10^{-6}	-	6.1
	35	3.03×10^{-6}	-	5.8
	40	4.17×10^{-6}	-	5.6
7	25	5.31×10^{-5}	3.60×10^{-2}	4.6
	30	6.92×10^{-5}	4.09×10^{-2}	1.3
	35	9.39×10^{-5}	4.22×10^{-2}	3.9
	40	1.33×10^{-4}	3.86×10^{-2}	3.2
8	10	2.33×10^{-5}	5.11×10^{-2}	18.5
	15	2.99×10^{-5}	7.26×10^{-2}	11.9
	25	2.40×10^{-5}	1.98×10^{-1}	3.1
	35	3.36×10^{-5}	2.74×10^{-1}	5.5
9	25	-	3.75×10^{-2}	7.3
	30	-	4.43×10^{-2}	6.0
	35	-	5.35×10^{-2}	3.5
	40	-	6.40×10^{-2}	2.5
10	10	2.49×10^{-6}	1.18×10^{-2}	9.7
	15	5.13×10^{-6}	1.58×10^{-2}	3.6
	25	1.93×10^{-5}	1.28×10^{-2}	6.8
	35	3.20×10^{-5}	1.32×10^{-2}	4.2

(continued)

TABLE 5 (continued)

Number	Temperature (°C)	k_1 ($\text{m}^6\text{.mol}^{-2}\text{.s}^{-1}$)	k_2 ($\text{m}^6\text{.mol}^{-2}\text{.s}^{-1}$)	Average relative error (%)
11	5	6.73×10^{-7}	-	17.8
	15	1.19×10^{-6}	-	17.5
	25	3.31×10^{-6}	-	22.3
	35	6.99×10^{-6}	-	22.6
12	5	1.59×10^{-6}	5.29×10^{-5}	7.9
	15	3.56×10^{-6}	1.04×10^{-4}	12.4
	25	7.22×10^{-6}	1.48×10^{-4}	10.1
14	15	1.63×10^{-7}	1.00×10^{-5}	13.8
	25	4.37×10^{-7}	1.15×10^{-5}	7.3
	30	5.29×10^{-7}	1.44×10^{-5}	4.1
15	25	3.73×10^{-5}	2.10×10^{-2}	3.3
	30	4.61×10^{-5}	2.56×10^{-2}	2.7
	35	5.50×10^{-5}	3.38×10^{-2}	3.2
	40	5.72×10^{-5}	4.92×10^{-2}	4.2
16	25	7.35×10^{-5}	2.17×10^{-2}	2.0
	30	9.69×10^{-5}	3.27×10^{-2}	2.1
	35	1.09×10^{-4}	6.78×10^{-2}	2.0
	40	1.40×10^{-4}	9.26×10^{-2}	2.5
17	5	2.28×10^{-5}	7.93×10^{-4}	7.5
	15	4.00×10^{-5}	3.08×10^{-3}	10.9
	25	7.79×10^{-5}	1.03×10^{-3}	9.1
18	25	1.89×10^{-6}	6.72×10^{-4}	6.7
	30	2.89×10^{-6}	7.77×10^{-4}	7.3
	35	2.62×10^{-6}	1.01×10^{-3}	6.7
	40	4.27×10^{-6}	1.01×10^{-3}	6.3
19	5	2.97×10^{-5}	7.23×10^{-3}	7.6
	10	4.13×10^{-5}	7.03×10^{-3}	4.7
	15	3.79×10^{-5}	2.05×10^{-2}	21.5
	25	6.23×10^{-5}	2.09×10^{-2}	3.5
20	5	2.06×10^{-5}	2.55×10^{-2}	5.2
	15	1.52×10^{-4}	7.15×10^{-2}	3.1
	25	2.53×10^{-4}	1.39×10^{-1}	14.8

(continued)

TABLE 5 (continued)

Number	Temperature (°C)	k_1 (m ⁶ .mol ⁻² .s ⁻¹)	k_2 (m ⁶ .mol ⁻² .s ⁻¹)	Average relative error (%)
21	25	1.70×10^{-4}	1.62×10^{-2}	6.5
	30	2.24×10^{-4}	1.56×10^{-2}	5.5
	35	2.64×10^{-4}	4.19×10^{-2}	3.7
	40	3.03×10^{-4}	1.16×10^{-1}	2.9

Figure 5

Relation between Arrhenius parameters for k_1 .
 $Ea_1 = 2.52 \times \ln(A_1) + 27.84$ and $R^2 = 0.94$.

Figure 6

Relation between Arrhenius parameters for k_2 .
 $Ea_2 = 2.33 \times \ln(A_2) + 12.73$ and $R^2 = 0.98$.

called the statistical compensation effect. This phenomena is well described by [Barrie \(2012\)](#).

We determine for each molecule the confidence ellipse area in order to evaluate the impact of statistical compensation effect on our parameters. The expression of the confidence ellipse area is given by Equation (32) where $\mathbf{b}$ is the vector of parameters ($\ln(A)$; E_a), $\hat{\mathbf{b}}$ is the estimation of ($\ln(A)$; E_a) represented by the center of the ellipse, $\mathbf{C}$ is the covariance matrix between parameters, $(p+1) = 2$ is the number of parameters, s^2 is the residual variance, $F_{\alpha;p;(n-p-1)}$ corresponds to the F -distribution value with a confidence level of $(1-\alpha)\%$ and n is the number of data points used to estimate $\mathbf{b}$.

$$(\mathbf{b} - \hat{\mathbf{b}})' \mathbf{C} (\mathbf{b} - \hat{\mathbf{b}}) \leq (p+1) \cdot s^2 \cdot F_{\alpha;p;(n-p-1)} \quad (32)$$

We represent in [Figure 7](#) the activation energy E_a versus $\ln(A)$ for kinetic constant k_1 . Indeed, this first

order kinetic constant has the greatest sensitivity on k_0 for most of the molecules which are generally close to $n = 1$. We limit our representation to molecules which are less impacted by statistical indetermination. The plot has been realized with the function ellipse of the R software with a 95% confidence level.

[Figure 7](#) confirms a correlation between activation energy and reaction preexponential factor A even with ellipse confidence area. Moreover the position of the molecule in this figure is clearly dependent on the reactivity of the molecule characterized by the degree of substitution and steric hindrance of the amine function. In fact, ethylenediamine which is the most reactive molecule has the lowest value of activation energy and preexponential factor. On the other side, a tertiary amine (3-dimethylaminopropanolamine) has the highest value of activation energy and preexponential factor.

Figure 7

Relation between Arrhenius parameters for k_1 .

TABLE 6

Corresponding number, structure, value of activation enthalpy and activation entropy determined according to transition state theory for amines of Figure 7

Number	Structure	$\Delta^\ddagger H$ (kJ.mol ⁻¹)	$\Delta^\ddagger S$ (J.mol ⁻¹ .K ⁻¹)
4	<chem>CC(C)NCCO</chem>	74	-18
5	<chem>CC(C)N(C)CCO</chem>	60	-68
6	<chem>CC(C)NCCO</chem>	51	-87
3	<chem>CC(C)NCCO</chem>	50	-99
12	<chem>CC(C)N(C)CCO</chem>	50	-79
7	<chem>CC(C)NCCO</chem>	45	-78
16	<chem>CC(C)N(C)CCO</chem>	29	-128
20	<chem>CC(C)NCCO</chem>	27	-128

6.2 Physical Compensation Effect

The compensation effect could also have a physical explanation. According to the transition state theory, activation energy can be related with activation enthalpy and preexponential factor with activation entropy according to Equation (33) and Equation (34) (Scacchi *et al.*, 1996), where $\Delta^\ddagger H$ is the activation enthalpy, R is the gas constant, T the temperature (here, we set at 298.15 K), k_B is the Boltzmann constant, h is the Planck constant, $\Delta^\ddagger S$ is the activation entropy and $c_0^{\Delta n^\ddagger}$ is the unitary concentration (1 000 mol.m⁻³) with $(1-\Delta n^\ddagger)$ which is the molecularity of the process (which is 3). Values of activation enthalpy and entropy are given in Table 6:

$$E_a = \Delta^\ddagger H - RT \quad (33)$$

$$A = \exp(1) \times \frac{k_B T}{h} \times \exp\left(\frac{\Delta^\ddagger S}{R}\right) c_0^{\Delta n^\ddagger} \quad (34)$$

For all molecules, values of activation entropy are negative. This variation of entropy, which reflects a reduction of molecular disorder, is due to the formation of two ions formed from three molecules (amine, water and carbon dioxide) in the transition state (Crooks and Donnellan, 1988). We notice that for linear primary amines 20 and 16, the reduction of molecular disorder is more important than for tertiary amines 4 and 5.

At the same time the enthalpy of activation is less important for primary amines than for tertiary amines.

In fact, primary amines have a higher reactivity with carbon dioxide in agreement with the lowest values of enthalpy. This higher reactivity is correlated with a larger reduction of entropy associated with carbamate formation. A smaller reduction of entropy in the case of carbonate formation for tertiary amine, specially for molecule 4 may also come from a smaller association of the reactant molecules in the transient state. In fact, hydrogen bonding between the water molecule associated to the amine function and the hydroxyl group of the amine should be weaker in the case of molecule 4 (propanolamine) than for ethanolamines.

In summary, a low activation enthalpy tends to be compensated by a large negative activation entropy correlated with strong association of water, CO₂ and amine in the transient state. This compensation phenomenon which partially explains the apparent relationship between activation energy and preexponential factor of k_1 and k_2 is certainly a new argument in favor of the termolecular mechanism.

CONCLUSION

Literature teems with experimental data about kinetic between amines and carbon dioxide. In this work, we have suggested a method in order to compare data from different authors.

We compare the apparent first order constants k_0 obtained from simple exponential fit of stopped flow data, as this technique is proven to be reproducible and adapted to study a large variety of amines.

Compilation of all data is represented in a 2D-plot of an empirical kinetic law with a power dependency of k_0 with the concentration. From this representation, structure-activity relationships are drawn for tertiary amines and primary or secondary amines with varying degree of steric hindrance. These data are also confronted with mechanisms proposed in the literature. Both termolecular and zwitterion mechanism are consistent to explain the reaction rates of all amines with CO_2 . However, it is generally impossible to know which step is rate-limiting in the zwitterion mechanism and to determine the three kinetic constants in the case where the two steps would contribute to the reaction rate.

The termolecular mechanism has the advantage to characterize each amine by only two kinetic constants which can be univocally derived from experimental data at different concentrations. With this model, a compensation effect between activation energy and preexponential factor has been observed which is a supplementary indication in favor of this mechanism.

REFERENCES

- Aleixo M., Prigent M., Gibert A., Porcheron F., Mokbel I., Jose J., Jacquin M. (2011) Physical and chemical properties of DMXTM solvents, *Energy Procedia* **4**, 148-155.
- Ali S.H. (2004) Kinetic study of the reaction of diethanolamine with carbon dioxide in aqueous and mixed solvent systems-application to acid gas cleaning, *Sep. Purifi. Technol.* **38**, 3, 281-296.
- Ali S.H. (2005) Kinetics of the reaction of carbon dioxide with blends of amines in aqueous media using the stopped-flow technique, *Int. J. Chem. Kinet.* **37**, 7, 391-405.
- Ali S.H., Merchant S.Q., Fahim M.A. (2000) Kinetic study of reactive absorption of some primary amines with carbon dioxide in ethanol solution, *Sep. Purifi. Technol.* **18**, 3, 163-175.
- Ali S.H., Merchant S.Q., Fahim M.A. (2002) Reaction kinetics of some secondary alkanolamines with carbon dioxide in aqueous solutions by stopped flow technique, *Sep. Purifi. Technol.* **27**, 2, 121-136.
- Ali S.H., Al-Rashed O., Merchant S.Q. (2010) Opportunities for faster carbon dioxide removal: A kinetic study on the blending of methyl monoethanolamine and morpholine with 2-amino-2-methyl-1-propanol, *Sep. Purifi. Technol.* **74**, 1, 64-72.
- Alper E. (1990a) Kinetics of Reactions of Carbon-Dioxide with Diglycolamine and Morpholine, *Chem. Eng. J.* **44**, 2, 107-111.
- Alper E. (1990b) Reaction mechanism and kinetics of aqueous solutions of 2-amino-2-methyl-1-propanol and carbon dioxide, *Ind. Eng. Chem. Res.* **29**, 8, 1725-1728.
- Atkins P., de Paula J. (2006) Physical Chemistry, 8th edn., Oxford University Press, Oxford.
- Barrie P.J. (2012) The mathematical origins of the kinetic compensation effect: 1. the effect of random experimental errors, *Phys. Chem. Chem. Phys.* **14**, 1, 318-326.
- Barth D., Tondre C., Lappai G., Delpuech J.J. (1981) Kinetic study of carbon dioxide reaction with tertiary amines in aqueous solutions, *J. Phys. Chem.* **85**, 24, 3660-3667.
- Barth D., Tondre C., Delpuech J.J. (1983) Stopped-flow determination of carbon dioxide-diethanolamine reaction mechanism: Kinetics of carbamate formation, *Int. J. Chem. Kinet.* **15**, 11, 1147-1160.
- Barth D., Tondre C., Delpuech J.J. (1984) Kinetics and mechanisms of the reactions of carbon dioxide with alkanolamines: a discussion concerning the cases of MDEA and DEA, *Chem. Eng. Sci.* **39**, 12, 1753-1757.
- Barth D., Tondre C., Delpuech J.-J. (1986) Stopped-flow investigations of the reaction kinetics of carbon dioxide with some primary and secondary alkanolamines in aqueous solutions, *Int. J. Chem. Kinet.* **18**, 4, 445-457.
- Bouhamra W., Bavbek O., Alper E. (1999) Reaction mechanism and kinetics of aqueous solutions of 2-amino-2-methyl-1,3-propanediol and carbon dioxide, *Chem. Eng. J.* **73**, 1, 67-70.
- Bavbek O., Alper E. (1999) Reaction mechanism and kinetics of aqueous solutions of primary and secondary alkanolamines and carbon dioxide, *Turkish J. Chem.* **23**, 3, 293-300.
- Caplow M. (1968) Kinetics of carbamate formation and breakdown, *J. Am. Chem. Soc.* **90**, 24, 6795-6803.
- Charpentier J.C. (1981) Mass-Transfer Rates in Gas-Liquid Absorbers and Reactors, in *Advances in Chemical Engineering*, Thomas B.D. (ed.), Academic Press.
- Chemicalize (2012a) <http://www.chemicalize.org/structure/#!/mol=CCNCCO&source=calculate>
- Chemicalize (2012b) <http://www.chemicalize.org/structure/#!/mol=CCCCNCCO&source=calculate>
- Chemicalize (2012c) <http://www.chemicalize.org/structure/#!/mol=2-amino-2-methylpropan-1%2C3-diol&source=fp>
- Chemicalize (2012d) <http://www.chemicalize.org/structure/#!/mol=2-amino-2-hydroxymethyl-1%2C3-propanediol&source=calculate>
- Contribution of Working Groups I, II and III to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change, Pachauri R.K., Reisinger A. (2008) *Climate Change 2007: Synthesis Report*, IPCC, Geneva.
- Conway W., Wang X., Fernandes D., Burns R., Lawrance G., Puxty G., Maeder M. (2011) Comprehensive kinetic and thermodynamic study of the reactions of $\text{CO}_2(\text{aq})$ and HCO_3^- with monoethanolamine (MEA) in aqueous solution, *J. Phys. Chem. A* **115**, 50, 14340-14349.
- Conway W., Wang X., Fernandes D., Burns R., Lawrance G., Puxty G., Maeder M. (2012) Toward Rational Design of Amine Solutions for PCC Applications: The Kinetics of the Reaction of $\text{CO}_2(\text{aq})$ with Cyclic and Secondary Amines in Aqueous Solution, *Environ. Sci. Technol.* **46**, 13, 7422-7429.
- Crooks J.E., Donnellan J.P. (1988) Kinetics of the formation of N, N-dialkylcarbamate from diethanolamine and carbon dioxide in anhydrous ethanol, *J. Chem. Soc. Perkin Trans. 2*, 2, 191-194.
- Crooks J.E., Donnellan J.P. (1989) Kinetics and mechanism of the reaction between carbon dioxide and amines in aqueous solution, *J. Chem. Soc. Perkin Trans. 2*, 4, 331-333.

- Crooks J.E., Donnellan J.P. (1990) Kinetics of the reaction between carbon dioxide and tertiary amines, *J. Organic Chem.* **55**, 4, 1372-1374.
- da Silva E.F., Svendsen H.F. (2004) *Ab Initio* Study of the Reaction of Carbamate Formation from CO₂ and Alkanolamines, *Ind. Eng. Chem. Res.* **43**, 13, 3413-3418.
- da Silva E.F., Svendsen H.F. (2007) Computational chemistry study of reactions, equilibrium and kinetics of chemical CO₂ absorption, *Int. J. Greenhouse Gas Control* **1**, 2, 151-157.
- Danckwerts P.V. (1970) Gas liquid reactions, McGraw-Hill Book Company, London.
- Danckwerts P.V. (1979) The reaction of CO₂ with ethanolamines, *Chem. Eng. Sci.* **34**, 4, 443-446.
- de Coninck H. (2010) Advocacy for carbon capture and storage could arouse distrust, *Nature* **463**, 7279, 293-293.
- Donaldson T.L., Nguyen Y.N. (1980) Carbon Dioxide Reaction Kinetics and Transport in Aqueous Amine Membranes, *Ind. Eng. Chem. Fundam.* **19**, 3, 260-266.
- Gordesli F.P., Alper E. (2011) The kinetics of carbon dioxide capture by solutions of piperazine and N-methyl piperazine, *Int. J. Global Warming* **3**, 1, 67-76.
- Hamborg E.S., Versteeg G.F. (2009) Dissociation Constants and Thermodynamic Properties of Amines and Alkanolamines from (293 to 353) K, *J. Chem. Eng. Data* **54**, 4, 1318-1328.
- Henni A., Li J., Tontiwachwuthikul P. (2008) Reaction Kinetics of CO₂ in Aqueous 1-Amino-2-Propanol, 3-Amino-1-Propanol, and Dimethylmonoethanolamine Solutions in the Temperature Range of 298–313 K Using the Stopped-Flow Technique, *Ind. Eng. Chem. Res.* **47**, 7, 2213-2220.
- Iida K., Sato H. (2012) Proton Transfer Step in the Carbon Dioxide Capture by Monoethanolamine: A Theoretical Study at the Molecular Level, *The Journal of Physical Chemistry B* **116**, 7, 2244-2248.
- Kadiwala S., Rayer A.V., Henni A. (2012) Kinetics of carbon dioxide (CO₂) with ethylenediamine, 3-amino-1-propanol in methanol and ethanol, and with 1-dimethylamino-2-propanol and 3-dimethylamino-1-propanol in water using stopped-flow technique, *Chem. Eng. J.* **179**, 262-271.
- Kumar P.S., Hogendoorn J.A., Versteeg G.F., Feron P.H.M. (2003) Kinetics of the reaction of CO₂ with aqueous potassium salt of taurine and glycine, *AIChE J.* **49**, 1, 203-213.
- Laurent A., Charpentier J.C. (1974) Aires interfaciales et coefficients de transfert de matière dans les divers types d'absorbants et de réacteurs gaz-liquide, *Chem. Eng. J.* **8**, 2, 85-101.
- Laurent A., Prost C., Charpentier J.-C. (1975) Détermination par méthode chimique des aires interfaciales et des coefficients de transfert de matière dans les divers types d'absorbants et de réacteurs gaz-liquide, *Journal de Chimie Physique* **72**, 2, 236-244.
- Lecomte F., Broutin P., Lebas E. (2010) Le captage du CO₂, des technologies pour réduire les émissions de gaz à effet de serre, Technip, Paris.
- Li J., Henni A., Tontiwachwuthikul P. (2007) Reaction Kinetics of CO₂ in Aqueous Ethylenediamine, Ethyl Ethanolamine, and Diethyl Monoethanolamine Solutions in the Temperature Range of 298–313 K, Using the Stopped-Flow Technique, *Ind. Eng. Chem. Res.* **46**, 13, 4426-4434.
- Littel R.J., van Swaaij W.P.M., Versteeg G.F. (1990a) Kinetics of Carbon Dioxide with tertiary Amines in aqueous solution, *AIChE J.* **36**, 11, 1633-1640.
- Littel R.J., Bos M., Knoop G.J. (1990b) Dissociation constants of some alkanolamines at 293, 303, 318, and 333 K, *J. Chem. Eng. Data* **35**, 3, 276-277.
- Liu L., Guo Q.X. (2001) Isokinetic relationship, isoequilibrium relationship, and enthalpy-entropy compensation, *Chem. Rev.* **101**, 3, 673-695.
- McCann N., Phan D., Wang X., Conway W., Burns R., Attalla M., Puxty G., Maeder M. (2009) Kinetics and Mechanism of Carbamate Formation from CO₂(aq), Carbonate Species, and Monoethanolamine in Aqueous Solution, *J. Phys. Chem. A* **113**, 17, 5022-5029.
- McCann N., Phan D., Fernandes D., Maeder M. (2011) A systematic investigation of carbamate stability constants by ¹H NMR, *Int. J. Greenhouse Gas Control* **5**, 3, 396-400.
- Pinsent B.R.W., Pearson L., Roughton F.J.W. (1956) The kinetics of combination of carbon dioxide with hydroxide ions, *Trans. Faraday Soc.* **52**, 1512-1520.
- Puxty G., Rowland R., Attalla M. (2010) Comparison of the rate of CO₂ absorption into aqueous ammonia and monoethanolamine, *Chem. Eng. Sci.* **65**, 2, 915-922.
- Rayer A.V., Sumon K.Z., Henni A., Tontiwachwuthikul P. (2011) Kinetics of the reaction of carbon dioxide (CO₂) with cyclic amines using the stopped-flow technique, *Energy Procedia* **4**, 140-147.
- Raynal L., Alix P., Bouillon P.A., Gomez A., le Febvre de Nailly M., Jacquin M., Kittel J., di Lella A., Mougin P., Trapy J. (2011) The DMXTM process: An original solution for lowering the cost of post-combustion carbon capture, *Energy Procedia* **4**, 779-786.
- Rinker E.B., Ashour S.S., Sandall O.C. (1996) Kinetics and Modeling of Carbon Dioxide Absorption into Aqueous Solutions of Diethanolamine, *Ind. Eng. Chem. Res.* **35**, 4, 1107-1114.
- Sartori G., Savage D.W. (1983) Sterically hindered amines for carbon dioxide removal from gases, *Ind. Eng. Chem. Fundam.* **22**, 2, 239-249.
- Scacchi G., Bouchy M., Foucaut J.M., Zahraa O. (1996) Cinétique et catalyse, Technique & documentation, Paris.
- Soli A.L., Byrne R.H. (2002) CO₂ system hydration and dehydration kinetics and the equilibrium CO₂/H₂CO₃ ratio in aqueous NaCl solution, *Marine Chem.* **78**, 2-3, 65-73.
- Taft R.W. (1976) Progress in physical organic chemistry, John Wiley & Sons Inc., New York.
- Ume C.S., Ozturk M.C., Alper E. (2012) Kinetics of CO₂ Absorption by a Blended Aqueous Amine Solution, *Chem. Eng. Technol.* **35**, 3, 464-468.
- Ume C.S., Alper E. (2012) Reaction kinetics of carbon dioxide with 2-amino-2-hydroxymethyl-1,3-propanediol in aqueous solution obtained from the stopped flow method, *Turkish J. Chem.* **36**, 3, 427-435.
- van Loo S., van Elk E.P., Versteeg G.F. (2007) The removal of carbon dioxide with activated solutions of methyl-diethanolamine, *J. Petrol. Sci. Eng.* **55**, 1-2, 135-145.
- Versteeg G.F., van Swaaij W.P.M. (1988a) On the Kinetics Between CO₂ and Alkanolamines Both in Aqueous and Non-Aqueous Solutions. 1. Primary and Secondary-Amines, *Chem. Eng. Sci.* **43**, 3, 573-585.

Versteeg G.F., van Swaaij W.P.M. (1988b) On the kinetics between CO₂ and alkanolamines Both in Aqueous and Non-Aqueous Solutions. 2. Tertiary amines, *Chem. Eng. Sci.* **43**, 3, 587-591.

Wang X., Conway W., Fernandes D., Lawrance G., Burns R., Puxty G., Maeder M. (2011) Kinetics of the Reversible Reaction of CO₂(aq) with Ammonia in Aqueous Solution, *J. Phys. Chem. A* **115**, 24, 6405-6412.

Xiang Q., Fang M., Yu H., Maeder M. (2012) Kinetics of the Reversible Reaction of CO₂(aq) and HCO₃⁻ with Sarcosine Salt in Aqueous Solution, *J. Phys. Chem. A* **116**, 42, 10276-10284.

Yu W.C., Astarita G., Savage D.W. (1985) Kinetics of carbon dioxide absorption in solutions of methyldiethanolamine, *Chem. Eng. Sci.* **40**, 8, 1585-1590.

Manuscript accepted in May 2013

Published online in December 2013

Copyright © 2013 IFP Energies nouvelles

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than IFP Energies nouvelles must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers, or to redistribute to lists, requires prior specific permission and/or a fee: Request permission from Information Mission, IFP Energies nouvelles, fax. +33 1 47 52 70 96, or revueogst@ifpen.fr.